



**SolarTech Power Solutions**

# **Communication Green Base Station ESS System**



## Overview

---

How ESS is connected to a base station?

Scheme 1: The classic scheme in which the base stations are only powered by grid electricity. Scheme 2: The PV modules are connected in series to obtain higher voltage and are connected to the AC bus of the base station through an inverter with MPPT function. ESS is connected to the 48 V DC bus through bidirectional DC/DC converter.

Can a base station power system be optimized according to local conditions?

The optimization of PV and ESS setup according to local conditions has a direct impact on the economic and ecological benefits of the base station power system. An improved base station power system model is proposed in this paper, which takes into consideration the behavior of converters.

Does loss of power converters affect the optimization of base station PV and ESS?

The main conclusions are as follows: The loss of power converters significantly affects the optimization of base station PV and ESS. Calculating with a fixed efficiency cannot accurately reflect the actual situation. The proposed evaluation method achieves a balance in LCC, initial investment, return on investment, and carbon emissions.

How long should PV ESS access capacity be optimized?

Except Scheme 1, the PV and ESS access capacity need to be optimized for the other two schemes. Considering the service life of PV modules, the optimization period is set to 15 years.

## Communication Green Base Station ESS System

---

### Contact Us

---

For catalog requests, pricing, or partnerships, please visit:  
<https://zegrzynek.pl>